

SPECIALS

Planks

Specials Vintage Sella

2016010

220 x 22 cm
15/4 mm



Packaging

| | |
|--------------------------|--------------------------|
| Boards per pack: | 6 boards |
| m ² per pack: | 2,904 m ² |
| Weight per pack: | 25 kg |
| Broken lengths per pack: | 25% minimal 60 cm length |
| Packs on a pallet: | 35 |

Dimensions

| | |
|--------------------|------------|
| Length: | 220 cm |
| Width: | 22 cm |
| Thickness (total): | 15 mm |
| Top layer: | 3,5-4,0 mm |

Dimensional tolerances according to EN13489

| | |
|---------------------------------------|------------------------|
| Length: | 0,20% |
| Width: | 0,2 mm |
| Thickness: | Total: 15 mm ± 0,2 mm |
| Top layer: | 3,5-4,0 mm |
| Height difference between the panels: | ≤0,2 mm |
| Squareness: | ≤0,2% across the width |
| Cup: | ≤0,2% across the width |
| Spring: | ≤0,1% over the length |
| Bend: | ≤1% over the length |

Other Specifications

| | |
|------------------------|--------------------------|
| Formaldehyde emission: | E1 |
| Insulation value: | R=0,11m ² k/w |
| Brinell hardness: | Average HB 3.7 |

Additional specifications

| | |
|-------------------|-------------------|
| Bevel: | Rounded |
| Construction: | 3-layerd |
| Moisture content: | 7% +/- 2% |
| Locking system: | Tongue and groove |

Instructions and Maintenance

Oil immediately after installation.
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).