

# MANSION COMFORT

## Mansion Comfort Dust Oak

2012972

152 x 22,8 cm  
7/0,55 mm

CE  
EN 14342-05

25 jaar  
Solidfloor™  
garantie



INTEGRATED  
SUBFLOOR  
INTEGRATED

### Packaging

Boards per pack:	6 boards
m <sup>2</sup> per pack:	2,08 m <sup>2</sup>
Weight per pack:	23,5 kg
Number of packs on a pallet:	24

### Dimensions

Length:	152 cm
Width:	22,8 cm
Thickness:	Total: 7 mm, including integrated sub floor Top layer: 0.55 mm

### Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 27C°
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, good
Acoustic reduction of impact sound:	Delat Lw: 15dB

### Specifications

Lightfastness (ISO 105-B02):	>6
Abrasion resistance (EN 660-2):	Group T
Heat transfer coefficient:	R=0,03m <sup>2</sup> k/w
Antistatic:	<2kV
Residual indentation (ISO 24343-1):	<0,05 mm
Dimensional stability:	<0.2%
Slip resistance (DIN 51130):	R9
Repetition factor:	4
Locking system:	Angle-angle
Bevel:	4-sided, micro bevel
Fire class:	Bfl-S1
VOC Emission:	A+

### Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.