

LOFT

Loft Light Oak

2013525

128,6 × 19,4 cm
Total: 7 mm



Packaging

Boards per pack:	9 stuks
m ² per pack:	2,25 m ²
Weight per pack:	17,4 kg

Dimensions

Length:	128,6 cm
Width:	19,4 cm
Thickness:	Totaal: 7 mm

Use

Usage class:	23 intensive domestic residential use 31 light commercial use
--------------	--

Dimensional tolerances according to EN13329

Squareness:	0,20 mm/m
-------------	-----------

Flatness of the assembled parts

Width:	concave 0.15%, convex ≤ 0.20 %
Length:	concave 0.50 %, convex ≤ 1.00 %
Height differences:	Ø < 0.10 mm, max. < 0.15 mm
Openings:	Ø ≤ 0.15 mm, max. ≤ 0.20 mm

Geometric properties

Length:	1286 ± 0.5mm
Width:	194 ± 0.1mm – bmax – bmin 0.2mm

Specifications

Heat transfer coefficient:	R ≤ 0.07m ² k/w
Lightfastness (ISO 105-B02):	Better than Level 4 Grayscale
Abrasion resistance (EN 13329):	AC3
Stain resistance:	Group 1-2 Level 5 Group 3 Level 4
Surface Structure:	Embossed
Bevel:	4-sided bevel
Locking system:	Angle-angle
Fire class:	Cfl-S1
Formaldehyde (EN 16516):	E1
VOC Emission:	A+

Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit www.solidfloor.com for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.

