

PROJECTS by Solidfloor™

Projects by Solidfloor

Projects

Plank Oak Brushed ASML PEFC

2012987

190 x 19 cm
14/3 mm

CE
EN 14342-05



Packaging

Boards per pack:	8 boards
m2 per pack:	2,888 m2
Weight per pack:	21 kg
Broken lengths per pack:	25% minimal 60 cm length

Dimensions

Length:	190 cm
Width:	19 cm
Thickness (total):	14 mm
Top layer:	2,5-3,0 mm

Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 14 mm ± 0,2 mm
Top layer:	2,5-3,0 mm
Height difference between the panels:	≤0,2 mm
Squareness:	≤0,2% across the width
Cup:	≤0,2% across the width
Spring:	≤0,1% over the length
Bend:	≤1% over the length

Other Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,1 m2 k/w
Brinell hardness:	Average HB 3.7

Additional specifications

Bevel:	1 mm
Construction:	3-layerd
Moisture content:	7% +/- 2%
Locking system:	Click

Instructions and Maintenance

Does not need to be oiled after installation.
Maintain with Solidfloor Parquet Polish. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).



EN 14342-05