

MANSION DRYBACK

Herringbone

Mansion Dryback Sand Oak

1209780

75 x 15 cm
2,5/0,55 mm

CE
EN 14342-05

25 jaar
Solidfloor™
garantie



Packaging

Boards per pack:	32 boards
m ² per pack:	3,6 m ²
Weight per pack:	15,48 kg
Number of packs on a pallet:	36

Dimensions

Length:	75 cm
Width:	15 cm
Thickness:	Total: 2.5 mm Top layer: 0.55 mm

Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 27C°
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, good
Acoustic reduction of impact sound:	3dB

Specifications

Lightfastness (ISO 105-B02):	>6
Abrasion resistance (EN 660-2):	Group T
Heat transfer coefficient:	R=0,02m ² k/w
Antistatic:	<2kV
Residual indentation (ISO 24343-1):	<0.05 mm
Dimensional stability:	<0.2%
Slip resistance (DIN 51130):	R9
Repetition factor:	6
Locking system:	N.a.
Bevel:	4-sided, micro bevel
Fire class:	Bfl-S1
VOC Emission:	A+

Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit www.solidfloor.com for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.