

# MANSION DRYBACK

Mansion Dryback Sand Oak

1209789

153,2 × 23,7 cm  
2,5/0,55 mm

CE  
EN 14342-05

25 jaar  
Solidfloor™  
garantie



## Packaging

Boards per pack:	10 boards
m <sup>2</sup> per pack:	3,62 m <sup>2</sup>
Weight per pack:	15,56 kg
Number of packs on a pallet:	36

## Dimensions

Length:	153,2 cm
Width:	23,7 cm
Thickness:	Total: 2.5 mm Top layer: 0.55 mm

## Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 27C°
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, good
Acoustic reduction of impact sound:	3dB

## Specifications

Lightfastness (ISO 105-B02):	>6
Abrasion resistance (EN 660-2):	Group T
Heat transfer coefficient:	R=0,02m <sup>2</sup> k/w
Antistatic:	<2kV
Residual indentation (ISO 24343-1):	<0,05 mm
Dimensional stability:	<0.2%
Slip resistance (DIN 51130):	R9
Repetition factor:	4
Locking system:	N.a.
Bevel:	4-sided, micro bevel
Fire class:	Bfl-S1
VOC Emission:	A+

## Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.