

RENOPARK

Herringbone

Rustic Grade Unfinished Look

2014500

75 x 15 cm
10/3 mm

CE
EN 14342-05

25 years
Solidfloor™
guarantee



Packaging

Boards per pack:	10 boards
m ² per pack:	1,125 m ²
Weight per pack:	7,2 kg
Broken lengths per pack:	Not allowed

Dimensions

Length:	75 cm
Width:	15 cm
Thickness (total):	10 mm
Top layer:	2,5-3,0 mm

Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 10 mm ± 0,2 mm
Top layer:	2,5-3,0 mm
Height difference between the panels:	≤0,2 mm
Squareness:	≤0,2% across the width
Cup:	≤0,2% across the width
Spring:	≤0,1% over the length
Bend:	≤1% over the length

Other Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,07m ² k/w
Brinell hardness:	Average HB 3.7

Additional specifications

Bevel:	1 mm 4-sided
Construction:	2-layerd
Moisture content:	7% +/- 2%
Locking system:	Tongue and groove

Instructions and Maintenance

Does not need to be oiled after installation.
Maintain with Solidfloor™ Ultimate Hardwax White & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).